abitex

Lohnke
Leder und Textil

smart linen

Z8143 002



IT

codice doganale
540761300.
utilizzo
imbottiti.
caratteristiche
87% poliestere (idrorepellente) - 13% resina,
altezza cm ± 140, peso ± 375 gr/m^2.
tintura
il prodotto é tinto in pezza.
lunghezza pezze
circa 30 mtl., disponibile anche al taglio con maggiorazione.
abrasione
90.000 cicli, ISO 12947-2.
solidità alla luce
4, ISO 105 B02.
solidità allo sfregamento
secco 5, umido 4/5, ISO 105 X12.
resistenza alla cucitura
ordito 4 mm, trama 4 mm, ISO 13936-2.
pilling
4/5, ISO 12945-2.
resistenza al fuoco
1IM - UNI 9175; EN 1021 1/2;
BS 5852:79 part 1 is 0+1; NFPA 260 Class 1;
California TB 117-2013; IMO FTP Code 307 part 8.
attenzione
sono ammesse leggere differenze di colore tra differenti partite, non ci assumiamo nessuna responsabilità per il trasferimento di colore/pigmenti causato da abbigliamento e accessori. le schede tecniche vengono costantemente aggiornate sul sito, pertanto vi invitiamo a verificare online i dati del prodotto su www.abitex.eu

EN

customs code
540761300.
use
upholstered furniture.
features
87% polyester (water repellent) - 13% resin,
width cm ± 140, weight ± 375 g/m^2.
dyeing
piece dyed product.
roll length
approx. 30 lm , can also be cut-to-length at an extra cost.
abrasion resistance
90.000 rubs, ISO 12947-2.
colour fastness to light
4, ISO 105 B02.
fastness to rubbing
dry 5 wet 4/5, ISO 105 X12.
seam slippage
warp 4 mm, weft 4 mm, ISO 13936-2.
pilling
4/5, ISO 12945-2.
fire resistance
1IM - UNI 9175; EN 1021 1/2;
BS 5852:79 part 1 is 0+1; NFPA 260 Class 1;
California TB 117-2013; IMO FTP Code 307 part 8.
attention
slight colour differences between different batches are allowed, we assume no responsibility for the transfer of colour/pigment caused by clothing and accessories. as technical data sheets are updated from time to time, we invite you to verify the latest document published for each item on the website www.abitex.eu


fireproof


imo-med


water repellent



year guarantee

CAMPIONE GRATUITO NON DESTINATO ALLA VENDITA (ART. 2 DPR 26.10.72 N° 633 E SUCCESSIVE INTEGRAZIONI) ESENTE DDT (ART. 4 C 6 DPR 627/78)