



## ROKE Standard

<b>Max. Lifting load</b>		12 000 kg
<b>Weight</b>	With hydraulic flange	30,5 kg
	Without hydraulic flange	29 kg
<b>Max. Interference circle diameter</b>		275 mm
<b>Height</b>		83 mm
<b>2 hydraulic couplings</b>	Nominal flow	65 l/min
	Pressure	max. 300 bar
<b>Safe connection</b>	Indicator pins	6 pieces

Indexator	Indexator-A	Baltrotor
<p>Fits on Indexator rotators:</p> <ul style="list-style-type: none"> <li>- GV12</li> <li>- G121</li> <li>- G141</li> </ul>	<p>Fits on Indexator rotators:</p> <ul style="list-style-type: none"> <li>- GV12-A</li> <li>- G121-A</li> <li>- G141-A</li> </ul>	<p>Fits on Baltrotor rotators:</p> <ul style="list-style-type: none"> <li>- GR104DB</li> <li>- GR105DB</li> </ul>
<p><b>This is the number that matters.</b></p>		

## CONNECTTECH

ConnectTech GmbH  
 Moselenweg 7  
 CH-4537 Wiedlisbach

032 533 13 83  
 info@connecttech-swiss.ch  
 connecttech-swiss.ch

